

# Super Cleaner

## Boatcare

Cleaning and degreasing



### PRODUCT DESCRIPTION

Super Cleaner is a highly concentrated cleaner. Removes wax, oil and contamination effectively. Suitable for hand and high pressure machine washing. Degreases and cleans with no damage to gelcoat or paintwork. Always use before waxing.

- \* Very effective degreasing when used at higher concentrations
- \* Easy to use
- \* Use before painting or waxing
- \* Also suitable for general cleaning on the boat, bilge/engine or car
- \* Biodegradable

### PRODUCT INFORMATION

<b>Colour</b>	YMB820
<b>Specific Gravity</b>	0.98
<b>Volume Solids</b>	30%
<b>Mix Ratio</b>	Light/medium cleaning - 4 to 8 black caps to 4 litres water. Heavier cleaning - use undiluted.
<b>VOC (As Supplied)</b>	0 g/lt
<b>Unit Size</b>	500 ml pH value of 10

### DRYING/OVERCOATING INFORMATION

#### Drying

#### Overcoating

#### Substrate Temperature

	5°C (41°F)	10°C (50°F)	23°C (73°F)	35°C (95°F)				
	Min	Max	Min	Max	Min	Max	Min	Max
Overcoated By								

### APPLICATION AND USE

<b>Preparation</b>	Rinse with fresh water and allow to dry.
<b>Method</b>	Choose appropriate mixing ratio. Add the required number of capfuls of Super Cleaner to fresh water. Apply Super Cleaner to a damp cloth or sponge, then wipe the whole surface to be cleaned using moderate pressure. Rinse with fresh water.
<b>Hints</b>	Mixing - Shake well before use.
<b>Some Important Points</b>	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
<b>Compatibility/Substrates</b>	Suitable for use on GRP, painted and metal surfaces.
<b>Application Methods</b>	Brush/Cloth/Sponge.

### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Super Cleaner to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. <b>TRANSPORTATION:</b> Super Cleaner should be kept in securely closed containers during transport and storage.
<b>Safety</b>	<b>GENERAL:</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line. <b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Super Cleaner cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

### IMPORTANT NOTES

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we*

Please refer to your local representative or visit [www.yachtpaint.com](http://www.yachtpaint.com) for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2018.

Super Cleaner  
Boatcare  
Cleaning and degreasing



---

*can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*

---

Please refer to your local representative or visit [www.yachtpaint.com](http://www.yachtpaint.com) for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2018.

Ref:3162 Super Cleaner Issue Date:13/12/2018